



### Descripción:

Tapones auditivos con anillos de agarre, triple borde. Provee un sellado más efectivo y facilita la inserción. No son irritantes, reutilizables (para ser utilizados más de una vez). Posee cordón para usarse alrededor del cuello para evitar su pérdida. NRR: 26 db.

### Presentación:

Talla N/A, código: NA6100101  
Color: Amarillo  
Unidad de Empaque: 100  
Presentación: Caja Principal con cajas pequeñas por unidades

### Característica y usos:

Anillos, reutilizable con cordón.  
Material: SILICONE 100%

Frecuencia en Hz	125	250	500	1000	2000	4000	800
Atenuación media	34.1	33.9	32.6	33.7	33.3	44.4	41.9
Desviación típica	4.9	6.3	6.5	4.2	3.5	5.1	4.5
Atenuación asumida	29.2	27.6	26.1	29.5	29.8	39.3	37.4



Conforme: CE en 352-2 / ANSI S3.19. 1974 - S12.6

Hearing Protective Device Test Report Number Q4949A Revision 0



Technician: Eileen Kline

Date of Report: 5/26/18

Date of testing: 5/14/18-5/24/18

Date of Sample Receipt: 5/14/18

Attenuation measurements have been performed according to the American National Standards Institute (ANSI) Specifications, ANSI S3.19-1974, using the experimenter-fit protocol, on the BDS PPE Group Co. Ltd. EC2001/EC2001C reusable insert-type hearing protector (test ID Q4949A). The specified threshold measurement data were obtained using ten normally-hearing listeners, six male and four female. These listeners were selected from a standby group of about 35 volunteers who regularly serve as listeners for measurements of this kind.

The measurements were made in a room designed for this purpose. All acoustic characteristics of the room meet the requirements outlined in ANSI S3.19-1974. The ambient noise levels in this room are below the limits specified in ANSI S3.19-1974, and open ear thresholds are used on a continuing basis to monitor the background noise levels. An automatic recording attenuator was used to record both open and occluded ear thresholds.

Each of ten subjects was tested three times at each of nine test frequencies. The attached Tables show grand mean attenuation values in decibels (dB) for each test signal along with group attenuation values. Standard deviations (S.D.) for the 30 different attenuation determinations for each test signal are also given. The results presented in this report pertain to the samples tested only.

Michael & Associates is accredited by the National Institute of Standards and Technology (NIST) National Laboratory Accreditation Program (NVLAP) for tests performed according to ANSI S3.19-1974, ANSI S12.6-2016, AS/NZ S1270:2002 and EN352 parts 1-8. These accreditation criteria encompass the requirements of international standard ISO 17025. This report may only be reproduced or transmitted electronically in its' entirety. This report shall not be used to claim product endorsement by NIST, NVLAP or by any agency of the U.S. Government. All measurement equipment are calibrated with instrumentation traceable to the NIST. Accreditation documentation can be viewed at [www.michaelassociates.com/data/documents/NVLAP-2017.pdf](http://www.michaelassociates.com/data/documents/NVLAP-2017.pdf).

*Use these laboratory-derived attenuation data for comparison purposes only. The amount of protection afforded in field use is often significantly lower depending on how the protectors are fitted and worn.*

A handwritten signature in black ink, appearing to read 'K Michael', is written over a horizontal line.

Kevin Michael, Ph.D., President

A handwritten date '5/26/18' in black ink is written over a horizontal line.

Date

**Individual and Summary Attenuation Data for  
Hearing Protective Devices**

Test Method: ANSI S3.19-1974  
 Manufacturer:  
 Model: EC2001/EC2001C

Position: Insert  
 Date: 5/26/18  
 Test ID: Q4949A

SUBJECT	Attenuation in dB								
	125	250	Center Frequency in Hz			3150	4000	6300	8000
	500	1000	2000						
1	31	27	33	34	36	43	36	38	47
	34	27	31	36	39	44	38	36	44
	33	30	38	38	39	45	37	35	46
2	42	37	43	37	32	50	44	46	43
	34	31	41	33	32	43	41	48	44
	38	32	38	35	33	44	41	47	41
3	40	37	40	40	39	41	45	50	45
	37	32	37	36	36	42	41	45	48
	31	34	36	36	37	42	41	46	48
4	41	39	43	44	40	47	39	41	44
	41	37	44	43	41	45	42	42	44
	38	35	40	40	39	42	42	43	46
5	37	36	36	35	37	45	48	43	48
	35	32	34	36	36	45	47	44	46
	33	31	32	32	36	46	47	43	46
6	32	26	32	26	31	38	35	35	46
	27	24	29	27	31	37	35	33	45
	26	24	31	26	32	38	36	34	46
7	28	26	33	32	35	37	36	37	48
	26	23	28	31	34	37	36	36	49
	24	26	33	31	36	35	35	35	48
8	30	27	33	28	37	42	40	38	40
	31	24	32	30	36	38	42	39	41
	27	23	30	29	38	39	39	36	40
9	40	38	41	33	36	46	49	47	47
	41	40	44	42	39	42	46	46	43
	31	38	44	36	39	40	48	48	44
10	36	32	39	33	36	34	34	43	44
	31	34	41	34	41	34	33	40	47
	29	28	32	33	37	37	35	40	47
MEANS	33.5	30.9	36.2	34.1	36.3	41.1	40.3	41.1	45.1
STD. DEV.	5.3	5.4	4.9	4.7	2.8	4.1	4.7	5.0	2.4

NRR = 26 dB

*Use these laboratory-derived data for comparison purposes only. The amount of protection afforded in field use is often significantly lower depending on how the protectors are fitted and worn.*

Manufacturer:  
Model: EC2001/EC2001C  
Position: Insert

Date: 5/26/18  
Test ID: Q4949A


Measurements were made according to American National Standards Institute Specifications ANSI S3.19-1974.

Center Frequency in Hz	Mean Attenuation in dB	Group Attenuation in dB	Standard Deviation in dB
125	33.5	64.4	5.3
250	30.9		5.4
500	36.2		4.9
1000	34.1		4.7
2000	36.3	188.1	2.8
3150	41.1		4.1
4000	40.3		4.7
6300	41.1	86.2	5.0
8000	45.1		2.4

Test Item: Q4949A



These data were obtained through measurements made at the laboratories of Michael & Associates, Inc., State College, PA, USA. Michael & Associates, Inc., is accredited to test to ANSI S3.19-1974, ANSI S12.6-2016, ANSI S12.42-2010, EN352 parts 1-8 and AS/NZ S1270:2002 by the National Institute of Standards and Technology (NIST) National Voluntary Laboratory Accreditation Program (NVLAP).

  
Kevin L. Michael, Ph.D.  
President

5/26/18  
Date