

Heavy duty nitrilo, puño cerrado

Descripción

Los guantes Nara Safe – HEAVY DUTY 100% nitrilo puño cerrado con forro interno de algodón son de uso industrial para la protección manual de las personas en los diferentes procesos, provee una capa con resistencia al rasgado conforme a la EN388; está fabricado en un material muy resistente de color azul sin costuras. Permite muy buena comodidad, confort, mejor ajuste, mayor destreza, estas especificaciones se traducen en una mayor productividad para el usuario y durabilidad para el elemento cuando se compara con otros guantes de protección general como los cueros.

Composición

Tejido: algodón interno nitrilo alta densidad externo

Puño: cerrado en algodón tejido

Longitud: mm 250-260

Características y usos

INFORMACIÓN GENERAL

Puño cerrado sin costura forro interno algodón jersey, Palma y dorso cubierta en nitrilo 100%, para destreza y confort del usuario, de tipo multiuso. Ideal para metal metálica, Tienen un tejido de 360° sin costuras que permite que las manos estén protegidas. Gracias a su recubrimiento en nitrilo tenemos mayor agarre, precisión y protección en contacto de químicos e hidrocarburos en las labores a realizar. Recomendado para manipulaciones precisas. Resistente a la abrasión, permitiendo excelente motricidad fina y protección en presencia de hidrocarburos permite sumergir hasta la muñeca.

USOS

Mantenimiento automotriz motos y aeronáuticos
Manejo de herramientas manual
Operaciones técnicas de construcción
Trabajos técnicos de mantenimiento industrial
Operaciones logísticas
Empaque y línea de producción
Imprenta archivo y documentos
Permite sumergir hasta la muñeca.

Certificaciones y estándares

CE EN388 4221

Propiedades físicas

Prueba	Nivel
ABRASIÓN	4
CORTE	2
RASGADO	2
PUNZADURA	1

CE EN388



4221

Presentación

REFERENCIA	TALLA	CÓDIGO DE BARRAS
NS1300212	9	4897040900089
NS1300213	10	4897040900096

UNIDAD DE EMPAQUE	12 pares
CAJA MÁSTER	120 unidades
EMPAQUE INDIVIDUAL	Etiqueta de cartón
PESO	70 gr
LONGITUD	250mm - 260mm
COLOR	Azul con blanco





Heavy duty nitrilo, puño cerrado

Tablas informativas

CE EN388 Protección mecánica

NIVEL DE ENSAYO	1	2	3	4	5
A. Resistencia a la abrasión (ciclos)	100	500	2000	8000	-----
B. Resistencia al corte (índice)	1.2	2.5	5.0	10.0	20.0
C. Resistencia al rasgado (newton)	10	25	50	75	-----
D. Resistencia a la punzadura (newton)	20	60	100	150	-----

Tallas y medidas

Referencia	S	M	L	XL
Tallas	7	8	9	10
Longitud en mm	230	240	250	260

Heavy duty nitrilo, puño cerrado / Certificaciones



In application of the Directive ref 89/686/EEC of the 21st of December 1989, concerning the alignment of member state legislation relating to personal protective equipment and the decrees n° 92-765, 766 and 768 of 29th of July 1992 concerning the transposition of this Directive into French law,

CTC

4, rue Hermann Frenkel - 69367 Cedex 07 - France
Tel +33 (0)4 72 76 10 10 - Fax +33 (0)4 72 72 76 10 00 - E-Mail : ctclyon@ctcgroupes.com - www.ctc.fr
Comité Professionnel de Développement Cuir Chaussure Maroquinerie - Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA
FR 86775649726

authorized by decree of the Ministry of Work, Employment and Health of the 20th of December 2010,

registered under the number 0075, published in OJEC, delivers :

CE TYPE EXAMINATION CERTIFICATE
0075/1182/162/01/12/0057 - EXT 03/08/12

To the following model of personal protective equipment :

- * protective glove against mechanical risks.
- * reference of the model : N3202
- * responsible for placing on the market :

Description of the protective glove, reference of technical rules verified in the context of the CE type examination and informations indicated on the product are detailed in the following pages of this certificate.

Drawn up in Lyon, on August 29th, 2012

Issued by Lionel GAUDILLERE



NOTA : Any modification to new items of the personal protective equipment object of this CE type approval certificate or any modification of the information contained in the manufacturer technical file which served for the delivery of the CE type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with law n° R. 4313 38 of the French Code of Work.

Heavy duty nitrilo, puño cerrado / Certificaciones



1. DESCRIPTION OF THE PROTECTIVE GLOVE

According to the technical file index : 01
 Reference : N3202
 Major Variant of the model : N3203
 Dated : AUGUST, 2012

Blue nitrile smooth Finish, Cotton jersey liner, Full Coat, knitted wrist Glove

Available sizes :

8 9 10 11

Visual description :



Material :

	Colour	Material	Gauges	Thikness
PALM	BLUE	NITRILE		
	WHITE	COTTON	36	
BACK	BLUE	NITRILE		
	WHITE	COTTON	36	
LINING				
CUFF	WHITE	COTTON	36	
BINDING				



Heavy duty nitrilo, puño cerrado / Certificaciones



2. PROTECTION SCOPE

Compliance with the essential requirements of the Directive 89/686/EEC has been verified by using following technical rules:

- * EN 420:2003+A1:2009 - General requirements for gloves and test methods
- * EN 388:2003 - Protective glove against mechanical risks
- * Directive 2002/61/CE : - This product fulfills the requirements given by the Directive.

References of test reports performed in order to verify the compliance with the requirements of the technical rules :

Laboratory	CTC Asia	CTC France	Other
EN 420	SH61836R1-11, SH60966-12, SH61157-12, SH61333-12		SH61004-11, SH61649-11
Azo	SH61004-11, SH60966-12		
EN 388	SH60993R1-11, SH61836R1-11, SH60966-12		

Performance levels offered against mechanical risks (EN 388:2003) are:

Abrasion resistance	Blade cut resistance	Tear strength resistance	Puncture resistance
4	2	2	1

The levels of performance have been measured on the palm

Heavy duty nitrilo, puño cerrado / Certificaciones



3. MARKING

Each glove is clearly marked with the following information:

- * Logo of the authorized representative:
- * CE marking
- * reference of the model: N3202
- * size
- * pictogram for mechanical risks followed by the performance levels
- * information pictogram

Marking example:





Heavy duty nitrilo, puño cerrado / Certificaciones

MANUFACTURER'S TECHNICAL FILE

Reference of the product	:	N3202
Technical file index	:	01
Last update	:	AUGUST, 2012



Heavy duty nitrilo, puño cerrado / Certificaciones

IDENTIFICATION

Reference of the product :	:	N3202
Major Variant of the model :	:	N3203
Technical file index :	:	01
Last update :	:	AUGUST, 2012

CE Type Examination Applicant :

Manufacturer :

Heavy duty nitrilo, puño cerrado / Certificaciones

GLOVE DESCRIPTION

Glove description :

Blue nitrile smooth Finish, Cotton jersey liner, Full Coat, knitted wrist Glove

Visual description:



Available sizes :

Minimum length of glove (mm)	Sizes
240	8
250	9
260	10
270	11

Glove constitution :

	Reference	Colour	Material	Surface mass	Gauges	Thickness
PALM		BLUE	NITRILE	550g/m ²		
		WHITE	COTTON	500g/m ²	36	
BACK		BLUE	NITRILE	550g/m ²		
		WHITE	COTTON	500g/m ²	36	
LINING						
CUFF		WHITE	COTTON	250g/m ²	36	
BINDING						



Heavy duty nitrilo, puño cerrado / Certificaciones

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protection Equipment Directive (89/686/CE).

This glove is designed for mechanical risks.

It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity : 5
PH of glove and lining is greater than 3.5 and lower than 9.5 : yes
Chromium VI lower than the detection limit : conform
Size : conform

Directive 2002/61/CE :

This product fulfills the requirements given by the Directive 2002/61/CE (Azo dyes).

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2003

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	2
Tear strength resistance	2
Puncture resistance	1

Heavy duty nitrilo, puño cerrado / Certificaciones


TEST REPORTS

Laboratory	CTC Asia	CTC France	Other
EN 420	SH61836R1-11, SH60966-12, SH61157-12, SH61333-12		SH61004-11, SH61649-11
Azo	SH61004-11, SH60966-12		
EN 388	SH60993R1-11, SH61836R1-11, SH60966-12		

MARKING - PACKAGING

Information printed on the glove :

Logo of the authorized representative :

Logo 

Glove's reference : N3202

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Marking example :



Method of marking on the glove :

PRINTING ON THE BACK OF GLOVE

Packaging :

1 PAIR/ BAG, 12PAIRS/POLYBAG; 240 PAIRS/CARTON



Heavy duty nitrilo, puño cerrado / Certificaciones

MEANS OF CONTROL

operate strictly according to ISO 9001 :2008



Heavy duty nitrilo, puño cerrado / Certificaciones

INSTRUCTION FOR USE

Glove reference : N3202

Available sizes : 8 9 10 11

Glove description :

Blue nitrile smooth Finish, Cotton jersey liner, Full Coat, knitted wrist Glove

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the Directive 89/686/CEE : innocuousness, comfort, solidity.

It has been subject to a CE type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

Applicable standards :

The glove meets the requirements of the standard EN 420 « General requirements for work glove ». Dexterity : 5

Moreover this glove has been designed for the following applications :



Application :
Mechanical hazard - EN 388



4221

Levels of performance

Abrasion resistance	4
Blade cut resistance	2
Tear resistance	2
Puncture resistance	1

Protection limit :

The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are only valid for the palm of the glove. The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated. These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire.

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.